

Fabric Requirements			
		Quilt 1	QUILT 2
Fabric 1	¹⁄₂ yd.	32401-18	32400-21
Fabric 2	FQ	32405-21	32405-23
Fabric 3	FQ	32404-17	32401-11
Fabric 4	¼ yd.	32403-17	32403-23
Fabric 5	FQ	32407-17	32402-13
Fabric 6 background	21⁄8 yds	9900-83	9900-83
Fabric 7 accent & binding	1¼ yds.	32402-17	32402-16



Cutting Fabric 1

Cut 2– 7¹/₂"x WOF strips. Subcut 8 – 7¹/₂"x 7¹/₂" squares

FABRIC 2

Cut 3 – 71/2" x 71/2" squares

Fabric 3

Cut 4 – 71/2"x 71/2" squares

Fabric 4

Cut 1–7¹/₂"x WOF strip. Subcut 5 – 7¹/₂"x 7¹/₂"

squares

Fabric 5

Cut 3 – 71/2"x 71/2" squares

Fabric 6

Cut $6 - 4\frac{1}{4}$ "xWOF strips for Strip Set 1

- Cut 3 11"xWOF strips for Strip Set 2
- Fabric 7
- Cut $6 2\frac{1}{2}$ "x WOF strips for binding.
- Cut 6 1"xWOF strips for Strip Sets 1 and 2
- Cut $1-7\frac{1}{2}$ "x WOF strip. Subcut 40 1"x $7\frac{1}{2}$ " strips for block frames
- Cut 2– 8¹/₂"x WOF strip. Subcut from first 8¹/₂"x WOF strip - 40 – 1"x 8¹/₂" strips for block frames

From second $8\frac{1}{2}x$ WOF strip first cut 10 – 1"x $8\frac{1}{2}$ " strips for block frames. Trim remaining fabric to $7\frac{1}{2}x$ WOF (approx. 30") Then cut 2 – $7\frac{1}{2}x$ $7\frac{1}{2}$ " squares for blocks and 10 – 1"x $7\frac{1}{2}$ " strips for block frames. *See diagram below*.

Construction

Strip Sets for Sashing Units

Strip Set 1

1. Stitch 1 - 1"xWOF Fabric 7 strip between 2 - 4¹/₄"xWOF Fabric 6 strips. Press seams toward Fabric 6. Make 3 Strip Sets.

Quilter Basics

Read instructions before beginning a project. All instructions include a ¼" seam allowance. 22" measurement is approximate. WOF–approximately 40".

2. From the 3 Strip Sets cut $20 - 3\frac{1}{2}$ " segments and 10 - 2" segments

Strip Set 2

1. Join 1 – 1"xWOF Fabric 7 strip and 1 –

11"xWOF Fabric 6 strip. Press seam toward Fabric 6. Make 3 strip sets.

2. From the 3 Strip Sets cut $24 - 3\frac{1}{2}$ " segments and 12 - 2" segments

3. Select $4 - 2^{"}$ and $8 - 3\frac{1}{2}^{"}$ segments to trim for "row ends". Trim 2-2" and $4-3\frac{1}{2}^{"}$ segments to measure $2^{"}x6\frac{1}{4}^{"}$ and $3\frac{1}{2}^{"}x6\frac{1}{4}^{"}$ including the Fabric 7 accent strip. *See diagram.*

Trim the remaining segments to measure $2^{x} 5^{3}$ and $3^{1}/2^{x} 5^{3}/4^{w}$ without the accent strip. *See diagram*.



Framing the Blocks

1. Stitch a 1"x $7\frac{1}{2}$ " Fabric 7 strip to opposite sides of each of the 25 – $7\frac{1}{2}$ "x $7\frac{1}{2}$ " squares. Press seam toward square.

2. Add a 1"x $8\frac{1}{2}$ " Fabric 7 strip to top and bottom of each of the blocks above. Press toward square.





Rows and Sashings

Rows:

1. Each row includes $5 - 8\frac{1}{2}x 8\frac{1}{2}$ " framed blocks, $4 - 3\frac{1}{2}x 8\frac{1}{2}$ " and $2 - 2x 8\frac{1}{2}$ " sashing segments. *See dia-gram.* Press seams toward framed blocks. Piece 5 Rows.



Sashing 1:

1. Each sashing strip includes $4 - 3\frac{1}{2}x 11\frac{1}{2}$ " units, $1 - 3\frac{1}{2}x 6\frac{1}{4}$ " unit and $1 - 3\frac{1}{2}x 5\frac{3}{4}$ " unit. *See diagram*. Press seams toward background. Piece 4 Sashing 1 Rows.

Sashing 2:

1. Repeat Step 1 using the 2" units to make top and bottom sashings.

Piece 2 sashings rows



Assemble Quilt

Join pieced rows and the sashing rows beginning and ending with a Sashing 2 row. Press seams toward sashings. Quilt should measure $55\frac{1}{2}$ " x $55\frac{1}{2}$ " with seams.

Finishing

Using a bias seam, join 6 – 2½"x WOF binding strips together end to end. Press seams open. Fold pieced binding in half, wrong sides together. Press. Layer, quilt and bind to complete this quilt.

moda

Size: 55"x55"